CARBOLITE®
a VERDER company

HTK - KOMOROVÁ PEC S KOVOVOU IZOLACÍ

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

The metallic HTK range of Carbolite high temperature furnaces consists of metal heaters made of Molybdenum or Tungsten.

The HTK series, made of metal, is available in four distinct sizes. The smaller HTKs with capacities of 8 and 25 liters are usually used in laboratories for research and development. The larger 80 and 120-litre furnaces are mostly utilized as pilot manufacturing systems or for large-scale production. The front door design of these furnaces allows for easy loading and unloading.

The metallic furnaces are constructed using tungsten (HTK W) or molybdenum (HTK MO), resulting in the highest possible purity of the inert atmosphere and final vacuum level. Upon request, a high vacuum upgrade is available. The most commonly used gases include Nitrogen, Argon, Hydrogen, and its mixtures.

The HTK series features heating elements and insulation made of either tungsten (HTK W) or molybdenum (HTK MO). A retort can be utilized to guide the gas flow, particularly for debinding applications or to enhance temperature uniformity. The maximum temperature for the HTK W is 2200 °C, while for the HTK MO, it is 1600 °C.

Kliknutím zobrazíte video

Produktové video: HTK - Komorová pec s kovovou izolací

PŘÍKLADY APLIKACÍ

carbon free atmosphere, metal injection moulding (MIM), metallization, sintering, thermal debinding, pyrolysis, synthesis, annealing, tempering

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

OVERVIEW

Furnace Type	Usable Volume	Maximální teplota	Number of heated zones	Debinding Option
HTK 8 MO/W	8	1600 °C / 2200 °C	1	Torch/ condensate trap
HTK 25 MO/W	25	1600 °C / 2200 °C	1	Torch/ condensate trap
HTK 80 MO	80	1600 °C	4	Torch/ condensate trap
HTK 120 MO	120	1450 °C	4	Torch/ condensate trap

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

HTK 8

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

HTK 25

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

HTK 80

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

HTK 120

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

	HTK 8	HTK 25	HTK 80	HTK 120
Usable space in the retort H x W x D [mm]	160 x 180 x 180	240 x 240 x 400	380 x 410 x 500	380 x 400 x 770
Number of plates*	3	3	40	60
Plate dimensions [cm²] *	225	860	930	930
Picture of sample rack				

* The displayed values refer to a typical retort layout. The specific arrangement can be customized to meet the requirements of the customer.

HTK - KOMOROVÁ PEC S KOVOVOU IZOLACÍ

EXPLANATION OF THE DEBINDING AND SINTERING PROCESS STEPS OF THE HTK-MIM-3 FURNACE

The HTK-MIM-3 furnace program enables debinding and sintering of MIM components in two stages. The program's progress is displayed in a diagram, and important parameters such as pressure, gas flow, and gas type are recorded. The debinding stage utilizes partial pressure and high nitrogen gas flow, while the sintering stage focuses on temperature uniformity, resulting in a consistent density of the MIM parts.

Kliknutím zobrazíte video

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

HTK - KOMOROVÁ PEC S KOVOVOU IZOLACÍ

INSIDE THE FURNACE

HTK 8 – 80 furnaces consist of:

1. Heaters
2. Retort
3. Radiation Shields
4. Thermocouple
5. Gas Inlet
6. Gas Outlet
7. Vacuum Gauge
8. Water-cooled vacuum vessel



Exemplary cross section of a HTK 8 molybdenum

HTK 120 furnaces consist of:

1. Heaters
2. Radiation Shields
3. Gas inlet
4. Gas Outlet



Heating cassette of the HTK 120, CAD drawing. Designed for highest lifetime and easy maintenance.

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

BINDER HANDLING OPTIONS HTK8 - 80

AFTERBURNER ASSEMBLY:

1. Retort
2. Gas outlet
3. Trace heating
4. Torch
5. Position controlled ball valve



Afterburner

The torch of the afterburner ensures controlled conversion of remaining flammable or toxic volatiles into non-flammable gases.

The condensate trap may be installed for binder handling. During the process the trap is cooled to condense the binder. After the process the trap can be heated to release the binder safely which has been liquified.

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

SOME HTK120 OPTIONS

AFTERBURNER ASSEMBLY:

1. Gas outlet
2. Trace heating
3. Torch
4. Position controlled ball valve
5. Fresh oil pump
6. Oil condenser

The stand alone safety purge tank ensures full safety for hydrogen applications. The furnace can only be started, if the tank is completely filled. Therefore the furnace is flood with nitrogen gas in case of major errors, such as power failure etc. The size is adjusted according to the furnace volume.



Heated gas outlet and vacuum line of the HTK 120

Stand alone safety purge tank

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

HIGH VACUUM APPLICATIONS

Cross section of HTK 8 with high vacuum upgrade. The turbo pump is at least connected via an DN100 flange.

1. Turbo pump
2. Vacuum valve
3. DN 100 flange



High vacuum upgrade



Schematic of a turbomolecular pump for high vacuum applications.

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

HTK - KOMOROVÁ PEC S KOVOVOU IZOLACÍ

CONTROLLER OPTIONS

The furnace is operated via a 12" or 19" touch panel controller. It provides an overview of the furnace and its behaviors and allows the user to preform any possible adjustments to the furnace.



Kliknutím zobrazíte video



Kliknutím zobrazíte video

- User friendly 12” touch panel, provides a detailed overview of the furnace status.
- Configuration of an automatic programm
- The smart software is mainly used for simple processes
- The full automatic function ensures full flexibility
- The pre-program ensures that the furnace is evacuated prior to heat treatment to ensure safety in case of any occuring errors
- The system is based on an industrial standard Siemens PLC ensuring full safety.

- Full visualization of the furnace with 19’’ touch panel, mainly for fully configured units or for the use of hydrogen (>5%)
- Configuration of an automatic program
- The automatic software is used for more complicated and hydrogen processes
- The CC-IPC1900 version additionally includes an industrial PC with standard windows software
- The system is based on an industrial standard Siemens F-PLC ensuring full safety even for hydrogen applications
- The pre-program ensures a fully automated leakage test which takes place in overpressure and vacuum

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

HTK - KOMOROVÁ PEC S KOVOVOU IZOLACÍ

EXAMPLES

HTK 8 MO/16-2G smart 8 L usable volume, 1600 °C, Argon, Forming gas

HTK 25 W/22-1G automatic 25 L usable volume, 2200 °C, Argon

HTK 80 MO/16-3G automatic 80 L usable volume, 1600 °C, Argon, Nitrogen, and optional hydrogen equipment

HTK 120 MO/14-3G automatic 120 L usable volume, 1400 °C, Argon, Nitrogen, Hydrogen, and partial pressure option

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

HTK - KOMOROVÁ PEC S KOVOVOU IZOLACÍ - FAQ

WHAT IS THE ADVANTAGE OF THE CHAMBER FURNACE DESIGN?

Chamber furnaces are quite easy to load and unload, due to the front loading concept. Smaller furnace can be loadaed manually, bigger units can be loaded by a manual fork lift. The rectangular design of the water cooled vacuum vessels allows the unit be be designed highly compact. This is why the units do not require much space in the workshop and are perfectly suited for laboratories. All HTK type furances are mounted on a single frame and can be easily delivered to customers all over the world. However, for bigger furnace volumes, the vessel is designed cylindrical, as for the HTK 120.

IS A GRAPHITE FURNACE BETTER?

This depends on the process. Some materials, such as stainless steel, 316L, titanium etc. cannot be heat treated in a graphite furnace, especially when the performance of the part is of importance. In such a case metallic furnaces are recommended due to their high purity atmospheres as well as hydrogen and high vacuum abilities.

WHY DOES HYDROGEN HEAT TREATMENT REQUIRE A METALLIC FURNACE?

In a graphite furnace, hydrogen would react with the graphite heating elements and insulation above 1000 °C. The higher the temperature, the faster the graphite parts wear which generates hydrocarbons and causes reactions with the sample. In a metallic furnace the resulting atmospthere is pure.

WHY IS THE INSULATION MADE FROM TUNGSTEN OR MOLYBDENUM?

The lower the variaty of materials inside the furnace chamber, the less is the cross-contamination inside the furnace. This leads to a purer atmosphere within the furnace. Furthermore, the working vacuum is better, due to high boiling points and low vapour pressure of the bespoken metals. The Carbolite vacuum furnace design consists of multiple layers of radiation shields to ensure very low energy consumption. Those layers act like a “mirror” reflecting the thermal radiation, hence insulating the furance. The remaining heat is taken away by cooling water surrounding the vacuum vessel.

WHAT IS THE ADVANTAGE OF (HYDROGEN) PARTIAL PRESSURE?

Carbolite enables adjustable pressure levels between 10 and 1000 mbar. With a variable pressure, the customer can adjust the gas density and therefore the Reynolds number as desired. This ensures a positve gas flow under reduced pressure, evaportating the binder at lower temperatures. This is advantageous for many applications. However, hydrogen partial pressure requires a lot expertise in order to handle it safely. We use dedicated software and hardware solutions to ensure full safety under these conditions.

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

TECHNICKÉ ÚDAJE (MODELY)

	HTK 8 MO/16-1G	HTK 25 MO/16-1G	HTK 80 MO/16-1G
Izolační materiál	Molybden	Molybden	Molybden
Rozměry: Vnější V x Š x H (mm)	2100 x 1300 x 1100	2200 x 1900 x 1800	2300 x 2100 x 2200
Celková hmotnost (kg)	1200	1700	2000
Využitelný prostor			
Objem (litry)	8	25	80
V x Š x H využitelný prostor bez retorty (mm)	200 x 200 x 200	250 x 250 x 400	400 x 400 x 500
V x Š x H využitelný prostor s retortou (mm)	200 x 180 x 180	230 x 230 x 400	380 x 380 x 500
Tepelné hodnoty			
Tmax vakuum (°C)	1600	1600	1600
Tmax atmosférického tlaku (°C)	1600	1600	1600
ΔT mezi 500 a 1500°C (K) podle DIN 17052	± 5	± 5	± 5
Max. rychlost ohřevu (K/min)	10	10	10
Čas chlazení (h)	6	6	8
Spojovací hodnoty			
Výkon (kW)	30	80	100
Napětí (V)	400	400 (3P)	400 (3P)
Proud (A)	75	3x 120	3x 150
Sériová pojistka (A)	3x 100	3x 160	3x 200
Vakuum (volba)			
Netěsnost - čistá, studená a prázdná pec (mbar l / s)	$5x10^{-3}$	$5x10^{-3}$	$5x10^{-3}$
Rozsah vakua v závislosti na čerpací jednotce	hrubé, jemné nebo vysoké vakuum	hrubé, jemné nebo vysoké vakuum	hrubé, jemné nebo vysoké vakuum
Požadavek chlazení vodou			

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

	HTK 8 MO/16-1G	HTK 25 MO/16-1G	HTK 80 MO/16-1G
Objem (l/min)	40	70	100
Maximální vstupní teplota (° C)	23	23	23
Dodávka plynu			
Dusík nebo argon, další na požádání (l/h)	200-2000	200-2000	200-2000
Regulátor	na vyžádání	na vyžádání	na vyžádání

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

	HTK 8 W/22-1G	HTK 25 W/22-1G	HTK 120 MO/16-3G MIM
Izolační materiál	Wolfram	Wolfram	Molybden
Rozměry: Vnější V x Š x H (mm)	2100 x 1300 x 1100	2200 x 1900 x 1800	-
Celková hmotnost (kg)	1300	1900	-
Využitelný prostor			
Objem (litry)	8	25	120
V x Š x H využitelný prostor bez retorty (mm)	200 x 200 x 200	250 x 250 x 400	-
V x Š x H využitelný prostor s retortou (mm)	180 x 180 x 200	230 x 230 x 400	-
Tepelné hodnoty			
Tmax vakuum (°C)	2200	2200	1600
Tmax atmosférického tlaku (°C)	2200	2200	1600
ΔT mezi 500 a 1500°C (K) podle DIN 17052	± 5	± 5	± 5
Max. rychlost ohřevu (K/min)	10	10	-
Čas chlazení (h)	6	6	<4
Spojovací hodnoty			
Výkon (kW)	45	100	100
Napětí (V)	400	400 (3P)	400 (3P)
Proud (A)	112	3x 150	3x 150
Sériová pojistka (A)	3x 160	3x 200	3x 200
Vakuum (volba)			
Netěsnost - čistá, studená a prázdná pec (mbar l / s)	-	-	$5x10^{-3}$
Rozsah vakua v závislosti na čerpací jednotce	hrubé, jemné nebo vysoké vakuum	hrubé, jemné nebo vysoké vakuum	hrubé, jemné nebo vysoké vakuum
Požadavek chlazení vodou			
Objem (l/min)	40	100	100

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům

	HTK 8 W/22-1G	HTK 25 W/22-1G	HTK 120 MO/16-3G MIM
Maximální vstupní teplota (° C)	23	23	23
Dodávka plynu			
Dusík nebo argon, další na požádání (l/h)	200-2000	200-2000	200-2000
Regulátor	na vyžádání	na vyžádání	na vyžádání

www.carbolite.com/htkmo

© Carbolite Gero Limited - www.carbolite.com
Výhrady k technickému řešení a nedostatkům